

UNCLASSIFIED

AD NUMBER
AD406097
NEW LIMITATION CHANGE
TO Approved for public release, distribution unlimited
FROM Distribution authorized to DoD only; Administrative/Operational Use; MAR 1963. Other requests shall be referred to Air Force Special Weapons Center, Attn: SWVWD, Kirtland AFB, NM.
AUTHORITY
afswc, per DTIC Form 55

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED

AD 406 097

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION, ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

ASTIA AVAILABILITY NOTICE

Qualified requestors may obtain copies of this report from ASTIA.

The findings in this report are not to be construed
as an official Department of the Army position.

BALLISTIC RESEARCH LABORATORIES

MEMORANDUM REPORT NO. 1462

MARCH 1963

**A METHOD FOR COMPUTING THE INTERACTION OF
TWO SPHERICAL BLAST WAVES**

R. C. Makino

Computing Laboratory

**For use only by recipients listed in back of report and by other Department
of Defense Agencies unless permission for further dissemination is obtained
from:**

**Commander
Air Force Special Weapons Center
ATTN: SWVWD
Kirtland Air Force Base, New Mexico**

RDT & E Project No. 1M010501A006

ABERDEEN PROVING GROUND, MARYLAND

BALLISTIC RESEARCH LABORATORIES

MEMORANDUM REPORT NO. 1462

RCMakino/jdk
Aberdeen Proving Ground, Md.
March 1963

**A METHOD FOR COMPUTING THE INTERACTION OF
TWO SPHERICAL BLAST WAVES**

ABSTRACT

The artificial viscosity method of von Neumann and Richtmyer for numerical solution of the partial differential equations of fluid flow is used to obtain a scheme for the numerical calculation of the interaction of two spherical blast waves in air.

TABLE OF CONTENTS

	Page
ABSTRACT	3
LIST OF SYMBOLS	7
INTRODUCTION.	9
INITIAL AND BOUNDARY CONDITIONS	12
COMPUTATIONAL SCHEME	17
CONCLUSION.	28
REFERENCES.	29
DISTRIBUTION LIST	31

LIST OF SYMBOLS

SUPERSCRIPTS

n refers to the time index.

o refers to time zero.

SUBSCRIPTS

k refers to the R space index.

l refers to the Z space index.

a refers to charge a.

b refers to charge b.

GREEK

α = an adjustable constant to steepen shock fronts.

ρ = density.

ROMAN

c = sound velocity.

E = specific internal energy.

$$J = \begin{vmatrix} \frac{\partial r}{\partial R} & \frac{\partial r}{\partial Z} \\ \frac{\partial z}{\partial R} & \frac{\partial z}{\partial Z} \end{vmatrix}.$$

$$K = \begin{vmatrix} \frac{\partial P}{\partial R} & \frac{\partial P}{\partial Z} \\ \frac{\partial z}{\partial R} & \frac{\partial z}{\partial Z} \end{vmatrix}.$$

$$L = \begin{vmatrix} \frac{\partial P}{\partial R} & \frac{\partial P}{\partial Z} \\ \frac{\partial r}{\partial R} & \frac{\partial r}{\partial Z} \end{vmatrix}.$$

p = pressure.

P = p + q.

$$q = \begin{cases} \frac{\alpha (\rho^0)^2 J}{\rho^3} \left(\frac{\partial \rho}{\partial t} \right)^2 & \text{if } \frac{\partial \rho}{\partial t} > 0, \\ 0 & \text{if } \frac{\partial \rho}{\partial t} \leq 0. \end{cases}$$

r = Eulerian coordinate perpendicular to the z -axis of symmetry.

r_a^0 = initial radius of charge a .

r_b^0 = initial radius of charge b .

R = Lagrange coordinate perpendicular to the Z -axis of symmetry.

ΔR = increment of Lagrange coordinate R .

t = time.

Δt = increment of time.

$u = \frac{\partial r(t, R, Z)}{\partial t}$ = r component of velocity.

$v = \frac{\partial z(t, R, Z)}{\partial t}$ = z component of velocity.

$w^0 = \rho^0 r^0 j^0$.

z = Eulerian coordinate of cylindrical symmetry.

z_a^0 = initial axial distance of center of charge a .

z_b^0 = initial axial distance of center of charge b .

Z = Lagrange coordinate of cylindrical symmetry.

ΔZ = increment of Lagrange coordinate Z .

INTRODUCTION

Axi-symmetric unsteady compressible flow problems arise extensively in military technology. Spherical blast waves and their interaction, explosions in vertically variable atmosphere, flow past axi-symmetric bodies, high-speed flow in axi-symmetric hypervelocity guns, shaped-charge gas-metal jet flow--all are of importance. The exact solution of the equations governing these flows which satisfies the appropriate initial and boundary conditions requires solving a system of non-linear hyperbolic partial differential equations in a two-space and one-time coordinate system, i.e., in three generalized dimensions. Presently, such exact solutions are not obtainable. The method of characteristics by which existence of solutions is shown opens the way for a numerical procedure, but this method requires a series of machine programs that escalates in complexity as the shock and characteristic discontinuity surfaces in the flow field interact and multiply the number of continuous zones bounded by discontinuity surfaces.

Von Neumann and Richtmyer proposed a method of numerical integration that changes the flow equations to the parabolic type. Although the solution is only approximate, the overall or essential nature of the solution is preserved; i.e., curves with momentum and energy discontinuities are warped into smooth but rapidly changing curves. (Stream surface material discontinuities, however, are not altered.) Therefore, the numerical procedure does not require the separate treatment of every continuous zone, and numerical solution with today's computing machines is quite feasible.

This is the method to be examined for calculation of the interaction of the blast waves from two spherical charges of initial radii r_a^0 and r_b^0 , since in this interaction the flow field is replete with discontinuity surfaces that complicate the problem.




FIGURE 1. ELAST INTERACTION

While this work is the theoretical extension of the experimental work done in References 1, 2, and 3 on project CLAW, with small modifications, the analysis can be extended to the other military problems previously listed.

FLOW EQUATIONS

The continuity equation in particle or Lagrange cylindrical coordinates for axi-symmetric flow is

$$(1) \quad \frac{\partial}{\partial t} (\rho r J) = 0, \quad J = \begin{vmatrix} \frac{\partial r}{\partial R} & \frac{\partial r}{\partial Z} \\ \frac{\partial z}{\partial R} & \frac{\partial z}{\partial Z} \end{vmatrix},$$

or

$$(2) \quad \rho r J = \rho^0 r^0 J^0 = w^0.$$

The momentum conservation equations are

$$(3) \quad \begin{cases} \frac{\partial u}{\partial t} = - \frac{r}{w^0} K, & K = \begin{vmatrix} \frac{\partial P}{\partial R} & \frac{\partial P}{\partial Z} \\ \frac{\partial z}{\partial R} & \frac{\partial z}{\partial Z} \end{vmatrix}, \\ \frac{\partial v}{\partial t} = \frac{r}{w^0} L, & L = \begin{vmatrix} \frac{\partial P}{\partial R} & \frac{\partial P}{\partial Z} \\ \frac{\partial r}{\partial R} & \frac{\partial r}{\partial Z} \end{vmatrix}, \end{cases}$$

where

$$(4) \quad \begin{cases} \frac{\partial r}{\partial t} = u, \\ \frac{\partial z}{\partial t} = v. \end{cases}$$

The energy conservation equation is

$$(5) \quad \frac{\partial E}{\partial t} = \frac{P}{\rho} \frac{\partial \rho}{\partial t},$$

where, in accordance with Reference 4, P is defined by

$$(6) \quad P = p + q ,$$

and q represents some artificial dissipative term. In accordance with References 5 and 7 we put

$$(7) \quad q = \begin{cases} \frac{\alpha (\rho^0)^2 J}{\rho^3} \left(\frac{\partial \rho}{\partial t} \right)^2 & \text{if } \frac{\partial \rho}{\partial t} > 0 , \\ 0 & \text{if } \frac{\partial \rho}{\partial t} \leq 0 . \end{cases}$$

The conservation equations above are supplemented by the thermodynamic equations of state

$$(8) \quad \begin{aligned} p &= p(E, \rho) , \\ c &= c(E, \rho) , \end{aligned}$$

which are assumed to be known.

The conservation equations above are hydrodynamically exact for $q = 0$; but for $q \neq 0$, the momentum and energy equations are modified, while the mass equation remains intact.

Equations (2) thru (8) are ten equations with the ten unknowns $(r, z, u, v, E, P, p, q, \rho, c)$, which are to be determined as functions of (t, R, Z) .

INITIAL AND BOUNDARY CONDITIONS

Two explosive charges of radii r_a^0 and r_b^0 with centers at z_a^0 and $z_b^0 = -z_a^0$ along the Z -axis (Figures 2 and 3), are initiated simultaneously at their centers. Assuming equilibrium flow and steady state Chapman-Jouget propagation of the detonation front, the initial explosion state can be calculated either




FIGURE 2. LAGRANGE SPACE




FIGURE 3. EULERIAN SPACE

by the Taylor progressive-wave approximation (Ref. 8), or by the numerical scheme to be subsequently described. In either case, the equation of state of the explosion products in chemical and thermodynamic equilibrium must be specified.

If the detonation process is to be calculated by the method outlined in this article, considering that the media ahead and behind the detonation front are not the same, the wave fronts must be treated as boundaries moving with the constant Chapman-Jouget velocity. The wave fronts form cones in the R, Z, t space (see Figure 2). Behind the detonation fronts the calculations use the equation of state of the explosion products. Ahead of the fronts are the undetonated portions of the charges.

When the detonation process is complete and the two explosion gases expand into the surrounding ambient air, shock waves are formed and propagate in an outward direction. These shocks eventually collide, and the two flows interact. The primary area of interest is in the nature of the interaction.

On each $t = \text{constant}$ plane (Figure 4) after the shock formation, two types of domains must be considered -- the explosion gas and air domains. Each has its own equations of state (8). Although shock surfaces are moving boundaries of discontinuities, the momentum and energy equations modified by the higher derivative dissipative term no longer permit this type of discontinuity surfaces to exist. In essence, such boundaries are smoothed out and no longer distinct.

In the Lagrange space (Figures 2 and 4), each explosion gas boundary remains a fixed circle in each $t = \text{constant}$ plane. The equations of these circles are

$$(9) \quad \begin{cases} R^2 + (Z - z_a)^2 = (r_a)^2, \\ R^2 + (Z - z_b)^2 = (r_b)^2. \end{cases}$$

Across these circles we assume dynamic equilibrium and laminar flow so that pressures and velocities normal to the stream surfaces are continuous. The stream surfaces remain as characteristics across which thermodynamic variables




FIGURE 4. $t = \text{CONSTANT PLANE}$

may be discontinuous, because the mass equation is unaltered in the modified system of conservation equations. Thus, the chemical composition and equations of state change abruptly across the explosion gas-air boundary.

COMPUTATIONAL SCHEME

The computational scheme for points interior to boundaries, i.e., points other than explosion gas-air boundaries, will be that adapted to this particular problem from Reference 5. The stability of this scheme is shown in Reference 6.


Let k, l, n be indices corresponding to the coordinates R, Z, t (Figure 5). Assume that on the $t = 0$ or $n = 0$ 'th plane all quantities, including

$$(10) \quad \left\{ \begin{array}{l} w_{k-\frac{1}{2}, l-\frac{1}{2}}^0 = \rho_{k-\frac{1}{2}, l-\frac{1}{2}}^0 \quad r_{k-\frac{1}{2}, l-\frac{1}{2}}^0 \quad J_{k-\frac{1}{2}, l-\frac{1}{2}}^0, \\ w_{k,l}^0 = \frac{1}{4} (w_{k-\frac{1}{2}, l-\frac{1}{2}}^0 + w_{k-\frac{1}{2}, l+\frac{1}{2}}^0 + w_{k+\frac{1}{2}, l-\frac{1}{2}}^0 + w_{k+\frac{1}{2}, l+\frac{1}{2}}^0), \\ \Delta R_{k,l} = \frac{1}{4} (\Delta R_{k-\frac{1}{2}, l-\frac{1}{2}} + \Delta R_{k-\frac{1}{2}, l+\frac{1}{2}} + \Delta R_{k+\frac{1}{2}, l-\frac{1}{2}} + \Delta R_{k+\frac{1}{2}, l+\frac{1}{2}}), \\ \Delta Z_{k,l} = \frac{1}{4} (\Delta Z_{k-\frac{1}{2}, l-\frac{1}{2}} + \Delta Z_{k-\frac{1}{2}, l+\frac{1}{2}} + \Delta Z_{k+\frac{1}{2}, l-\frac{1}{2}} + \Delta Z_{k+\frac{1}{2}, l+\frac{1}{2}}), \end{array} \right.$$

are known at the pre-determined points

$$R_{k-\frac{1}{2}, l-\frac{1}{2}}, Z_{k-\frac{1}{2}, l-\frac{1}{2}} \quad \text{and} \quad R_{k,l}, Z_{k,l}.$$

(This grid spacing in the R, Z space may require changing at some time t^n , depending on the gradients of the solution.) Also, assume that on the successive $(n-\frac{1}{2})$ th and $(n-1)$ th constant time planes, the following quantities have been computed for all values of the indices k, l up to k, l :



$(n-\frac{1}{2})$ th plane

$$(\Delta t)^{n-\frac{1}{2}},$$

$$u_{k-\frac{1}{2}, l-\frac{1}{2}}^{n-\frac{1}{2}}, v_{k-\frac{1}{2}, l-\frac{1}{2}}^{n-\frac{1}{2}}.$$

$(n-1)$ th plane

$$t^{n-1},$$

$$r_{k,l}^{n-1}, z_{k,l}^{n-1},$$

$$E_{k-\frac{1}{2}, l-\frac{1}{2}}^{n-1}, \rho_{k-\frac{1}{2}, l-\frac{1}{2}}^{n-1}, P_{k-\frac{1}{2}, l-\frac{1}{2}}^{n-1}, P_{k-\frac{1}{2}, l-\frac{1}{2}}^{n-1}, c_{k-\frac{1}{2}, l-\frac{1}{2}}^{n-1}.$$

The computational network sequence is chosen such that on each constant n plane k varies along constant l strips.

On the n th plane, r and z are approximated using the velocity definitions of equation (4).

$$(11) \quad \left\{ \begin{array}{l} r_{k,l}^n = r_{k,l}^{n-1} + u_{k,l}^{n-\frac{1}{2}} \Delta t^{n-\frac{1}{2}}, \\ z_{k,l}^n = z_{k,l}^{n-1} + v_{k,l}^{n-\frac{1}{2}} \Delta t^{n-\frac{1}{2}}. \end{array} \right.$$

At half points r, z are obtained by averaging the values at the neighboring whole points.

$$(12) \quad \left\{ \begin{array}{l} r_{k - \frac{1}{2}, l - \frac{1}{2}}^n = \frac{1}{4}(r_{k-1, l-1}^n + r_{k, l-1}^n + r_{k-1, l}^n + r_{k, l}^n) , \\ z_{k - \frac{1}{2}, l - \frac{1}{2}}^n = \frac{1}{4}(z_{k-1, l-1}^n + z_{k, l-1}^n + z_{k-1, l}^n + z_{k, l}^n) . \end{array} \right.$$

From these values the gradients of r, z are approximated by the difference quotients

$$(13) \quad \left\{ \begin{array}{l} \left(\frac{\partial r}{\partial R} \right)_{k - \frac{1}{2}, l - \frac{1}{2}}^n = \frac{1}{\Delta R_{k - \frac{1}{2}, l - \frac{1}{2}}} \left(\frac{r_{k, l-1}^n + r_{k, l}^n}{2} - \frac{r_{k-1, l-1}^n + r_{k-1, l}^n}{2} \right) , \\ \left(\frac{\partial z}{\partial R} \right)_{k - \frac{1}{2}, l - \frac{1}{2}}^n = \frac{1}{\Delta R_{k - \frac{1}{2}, l - \frac{1}{2}}} \left(\frac{z_{k, l-1}^n + z_{k, l}^n}{2} - \frac{z_{k-1, l-1}^n + z_{k-1, l}^n}{2} \right) , \\ \left(\frac{\partial r}{\partial Z} \right)_{k - \frac{1}{2}, l - \frac{1}{2}}^n = \frac{1}{\Delta Z_{k - \frac{1}{2}, l - \frac{1}{2}}} \left(\frac{r_{k-1, l}^n + r_{k, l}^n}{2} - \frac{r_{k-1, l-1}^n + r_{k, l-1}^n}{2} \right) , \\ \left(\frac{\partial z}{\partial Z} \right)_{k - \frac{1}{2}, l - \frac{1}{2}}^n = \frac{1}{\Delta Z_{k - \frac{1}{2}, l - \frac{1}{2}}} \left(\frac{z_{k-1, l}^n + z_{k, l}^n}{2} - \frac{z_{k-1, l-1}^n + z_{k, l-1}^n}{2} \right) , \end{array} \right.$$

which give for the Jacobian

$$(14) \quad J_{k - \frac{1}{2}, l - \frac{1}{2}}^n = \begin{vmatrix} \left(\frac{\partial r}{\partial R}\right)_{k - \frac{1}{2}, l - \frac{1}{2}}^n & \left(\frac{\partial r}{\partial Z}\right)_{k - \frac{1}{2}, l - \frac{1}{2}}^n \\ \left(\frac{\partial z}{\partial R}\right)_{k - \frac{1}{2}, l - \frac{1}{2}}^n & \left(\frac{\partial z}{\partial Z}\right)_{k - \frac{1}{2}, l - \frac{1}{2}}^n \end{vmatrix}.$$

The continuity equation (2) now gives the density as

$$(15) \quad \rho_{k - \frac{1}{2}, l - \frac{1}{2}} = \frac{w_{k - \frac{1}{2}, l - \frac{1}{2}}^0}{r_{k - \frac{1}{2}, l - \frac{1}{2}}^n J_{k - \frac{1}{2}, l - \frac{1}{2}}^n},$$

which gives the approximate time derivative of the density as

$$(16) \quad \left(\frac{\partial \rho}{\partial t}\right)_{k - \frac{1}{2}, l - \frac{1}{2}}^{n - \frac{1}{2}} = \frac{\rho_{k - \frac{1}{2}, l - \frac{1}{2}}^n - \rho_{k - \frac{1}{2}, l - \frac{1}{2}}^{n-1}}{(\Delta t)^{n - \frac{1}{2}}}.$$

The artificial viscosity term is evaluated from (7):

$$(17) \quad q_{k - \frac{1}{2}, l - \frac{1}{2}}^{n - \frac{1}{2}} = \begin{cases} \frac{\alpha(\rho_{k - \frac{1}{2}, l - \frac{1}{2}}^0)^2 \frac{1}{2} (J_{k - \frac{1}{2}, l - \frac{1}{2}}^n + J_{k - \frac{1}{2}, l - \frac{1}{2}}^{n-1})}{\frac{1}{8} (\rho_{k - \frac{1}{2}, l - \frac{1}{2}}^n + \rho_{k - \frac{1}{2}, l - \frac{1}{2}}^{n-1})^3} \dots \\ \dots \left[\left(\frac{\partial \rho}{\partial t}\right)_{k - \frac{1}{2}, l - \frac{1}{2}}^{n - \frac{1}{2}} \right]^2 \\ \text{if } \left(\frac{\partial \rho}{\partial t}\right)_{k - \frac{1}{2}, l - \frac{1}{2}}^{n - \frac{1}{2}} > 0, \\ 0 \text{ if } \left(\frac{\partial \rho}{\partial t}\right)_{k - \frac{1}{2}, l - \frac{1}{2}}^{n - \frac{1}{2}} \leq 0. \end{cases}$$

The energy conservation equation (5) and the equation of state (8) can be used to calculate the thermodynamic variables $E_{k - \frac{1}{2}, l - \frac{1}{2}}^n$, $p_{k - \frac{1}{2}, l - \frac{1}{2}}^n$,

and $c_{k - \frac{1}{2}, l - \frac{1}{2}}^n$ by simultaneous solution:

$$(18) \quad \left\{ \begin{aligned} E_{k - \frac{1}{2}, l - \frac{1}{2}}^n &= (\Delta t)^{n - \frac{1}{2}} \left[E_{k - \frac{1}{2}, l - \frac{1}{2}}^{n - \frac{1}{2}} + \frac{1}{2} \left(\frac{p_{k - \frac{1}{2}, l - \frac{1}{2}}^n + q_{k - \frac{1}{2}, l - \frac{1}{2}}^{n - \frac{1}{2}}}{(\rho_{k - \frac{1}{2}, l - \frac{1}{2}}^n)^2} \right. \right. \\ &\quad \left. \left. + \frac{p_{k - \frac{1}{2}, l - \frac{1}{2}}^{n - \frac{1}{2}}}{(\rho_{k - \frac{1}{2}, l - \frac{1}{2}}^{n - \frac{1}{2}})^2} \right) \left(\frac{\partial p}{\partial t} \right)_{k - \frac{1}{2}, l - \frac{1}{2}}^{n - \frac{1}{2}} \right], \\ p_{k - \frac{1}{2}, l - \frac{1}{2}}^n &= p \left(E_{k - \frac{1}{2}, l - \frac{1}{2}}^n, \rho_{k - \frac{1}{2}, l - \frac{1}{2}}^n \right), \\ c_{k - \frac{1}{2}, l - \frac{1}{2}}^n &= c \left(E_{k - \frac{1}{2}, l - \frac{1}{2}}^n, \rho_{k - \frac{1}{2}, l - \frac{1}{2}}^n \right). \end{aligned} \right.$$

The second and third equations in (18) will differ for air and explosion gas.

P is approximated by

$$P_{k - \frac{1}{2}, l - \frac{1}{2}}^n = p_{k - \frac{1}{2}, l - \frac{1}{2}}^n + q_{k - \frac{1}{2}, l - \frac{1}{2}}^{n - \frac{1}{2}}.$$

With the quantities computed previously, the following can be calculated:

$$\begin{aligned}
 & A_{k - \frac{1}{2}, l - \frac{1}{2}}^n = \left[\left(\frac{\partial r}{\partial R} \right)_{k - \frac{1}{2}, l - \frac{1}{2}}^n \right]^2 + \left[\left(\frac{\partial z}{\partial R} \right)_{k - \frac{1}{2}, l - \frac{1}{2}}^n \right]^2 \\
 & \quad + \left[\left(\frac{\partial r}{\partial Z} \right)_{k - \frac{1}{2}, l - \frac{1}{2}}^n \right]^2 + \left[\left(\frac{\partial z}{\partial Z} \right)_{k - \frac{1}{2}, l - \frac{1}{2}}^n \right]^2, \\
 & B_{k - \frac{1}{2}, l - \frac{1}{2}}^n = \left| \frac{J_{k - \frac{1}{2}, l - \frac{1}{2}}^n}{c_{k - \frac{1}{2}, l - \frac{1}{2}} (1.25 A_{k - \frac{1}{2}, l - \frac{1}{2}}^n)^{\frac{1}{2}}} \right|, \\
 & C_{k - \frac{1}{2}, l - \frac{1}{2}}^n = \begin{cases} B_{k - \frac{1}{2}, l - \frac{1}{2}}^n & \text{if } \left(\frac{\partial \rho}{\partial t} \right)_{k - \frac{1}{2}, l - \frac{1}{2}}^{n - \frac{1}{2}} \leq 0, \\ \left| \frac{0.225 \rho_{k - \frac{1}{2}, l - \frac{1}{2}}^n J_{k - \frac{1}{2}, l - \frac{1}{2}}^n}{\alpha A_{k - \frac{1}{2}, l - \frac{1}{2}}^n \left(\frac{\partial \rho}{\partial t} \right)_{k - \frac{1}{2}, l - \frac{1}{2}}^{n - \frac{1}{2}}} \right| & \text{if } \left(\frac{\partial \rho}{\partial t} \right)_{k - \frac{1}{2}, l - \frac{1}{2}}^{n - \frac{1}{2}} > 0. \end{cases}
 \end{aligned}
 \tag{19}$$

Minimizing, the following is obtained:

If $k = 1, l = 1,$

$$(20) \quad D_{\frac{1}{2}, \frac{1}{2}}^n = \text{MIN} \left(B_{\frac{1}{2}, \frac{1}{2}}^n, C_{\frac{1}{2}, \frac{1}{2}}^n \right).$$

If $k = 1, l > 1,$

$$(21) \quad D_{\frac{1}{2}, l - \frac{1}{2}}^n = \text{MIN} \left(B_{\frac{1}{2}, l - \frac{1}{2}}^n, C_{\frac{1}{2}, l - \frac{1}{2}}^n, D_{\max(k - \frac{1}{2}), l - \frac{1}{2}}^n \right).$$

If $k > 1,$

$$(22) \quad D_{k - \frac{1}{2}, l - \frac{1}{2}}^n = \text{MIN} \left(B_{k - \frac{1}{2}, l - \frac{1}{2}}^n, C_{k - \frac{1}{2}, l - \frac{1}{2}}^n, D_{k - \frac{1}{2}, l - \frac{1}{2}}^n \right).$$

(Note: The calculation above assumes that k increases on constant l strips.)

Time increments are calculated from

$$(23) \quad \begin{cases} \Delta t^{n + \frac{1}{2}} = \text{MIN} \left(1.4 \Delta t^{n - \frac{1}{2}}, D_{\max(k - \frac{1}{2}), \max(l - \frac{1}{2})}^n \right), \\ \Delta t^n = \frac{1}{2} \left(\Delta t^{n - \frac{1}{2}} + \Delta t^{n + \frac{1}{2}} \right), \end{cases}$$

and the time from

$$(24) \quad \begin{cases} t^n = t^{n-1} + \Delta t^{n - \frac{1}{2}}, \\ t^{n + \frac{1}{2}} = t^{n - \frac{1}{2}} + \Delta t^n. \end{cases}$$

The P, r, z gradients at k-1, l-1 are approximated by:

$$\left\{ \begin{aligned} \left(\frac{\partial P}{\partial R} \right)_{k-1, l-1}^n &= \frac{1}{\Delta R_{k-1, l-1}} \left(\frac{P^n}{k - \frac{1}{2}, l - \frac{1}{2}} + \frac{P^n}{k - \frac{1}{2}, l - \frac{1}{2}} - \frac{P^n}{k - \frac{1}{2}, l - \frac{1}{2}} + \frac{P^n}{k - \frac{1}{2}, l - \frac{1}{2}} \right), \\ \left(\frac{\partial P}{\partial Z} \right)_{k-1, l-1}^n &= \frac{1}{\Delta Z_{k-1, l-1}} \left(\frac{P^n}{k - \frac{1}{2}, l - \frac{1}{2}} + \frac{P^n}{k - \frac{1}{2}, l - \frac{1}{2}} - \frac{P^n}{k - \frac{1}{2}, l - \frac{1}{2}} + \frac{P^n}{k - \frac{1}{2}, l - \frac{1}{2}} \right), \\ \left(\frac{\partial r}{\partial R} \right)_{k-1, l-1}^n &= \frac{1}{\Delta R_{k-1, l-1}} \left(\frac{r^n}{k - \frac{1}{2}, l - \frac{1}{2}} + \frac{r^n}{k - \frac{1}{2}, l - \frac{1}{2}} - \frac{r^n}{k - \frac{1}{2}, l - \frac{1}{2}} + \frac{r^n}{k - \frac{1}{2}, l - \frac{1}{2}} \right), \\ \left(\frac{\partial r}{\partial Z} \right)_{k-1, l-1}^n &= \frac{1}{\Delta Z_{k-1, l-1}} \left(\frac{r^n}{k - \frac{1}{2}, l - \frac{1}{2}} + \frac{r^n}{k - \frac{1}{2}, l - \frac{1}{2}} - \frac{r^n}{k - \frac{1}{2}, l - \frac{1}{2}} + \frac{r^n}{k - \frac{1}{2}, l - \frac{1}{2}} \right), \\ \left(\frac{\partial z}{\partial R} \right)_{k-1, l-1}^n &= \frac{1}{\Delta R_{k-1, l-1}} \left(\frac{z^n}{k - \frac{1}{2}, l - \frac{1}{2}} + \frac{z^n}{k - \frac{1}{2}, l - \frac{1}{2}} - \frac{z^n}{k - \frac{1}{2}, l - \frac{1}{2}} + \frac{z^n}{k - \frac{1}{2}, l - \frac{1}{2}} \right), \\ \left(\frac{\partial z}{\partial Z} \right)_{k-1, l-1}^n &= \frac{1}{\Delta Z_{k-1, l-1}} \left(\frac{z^n}{k - \frac{1}{2}, l - \frac{1}{2}} + \frac{z^n}{k - \frac{1}{2}, l - \frac{1}{2}} - \frac{z^n}{k - \frac{1}{2}, l - \frac{1}{2}} + \frac{z^n}{k - \frac{1}{2}, l - \frac{1}{2}} \right). \end{aligned} \right. \quad (25)$$

From these results, K and L are evaluated as:

$$(26) \quad \left\{ \begin{array}{l} K_{k-1, l-1}^n = \begin{vmatrix} \left(\frac{\partial P}{\partial R}\right)_{k-1, l-1}^n & \left(\frac{\partial z}{\partial R}\right)_{k-1, l-1}^n \\ \left(\frac{\partial P}{\partial Z}\right)_{k-1, l-1}^n & \left(\frac{\partial z}{\partial Z}\right)_{k-1, l-1}^n \end{vmatrix} , \\ L_{k-1, l-1}^n = \begin{vmatrix} \left(\frac{\partial P}{\partial R}\right)_{k-1, l-1}^n & \left(\frac{\partial r}{\partial R}\right)_{k-1, l-1}^n \\ \left(\frac{\partial P}{\partial Z}\right)_{k-1, l-1}^n & \left(\frac{\partial r}{\partial Z}\right)_{k-1, l-1}^n \end{vmatrix} . \end{array} \right.$$

The momentum conservation equations (3) give the accelerations

$$(27) \quad \left\{ \begin{array}{l} \left(\frac{\partial u}{\partial t}\right)_{k-1, l-1}^n = - \frac{r_{k-1, l-1}^n K_{k-1, l-1}^n}{w_{k-1, l-1}^0} , \\ \left(\frac{\partial v}{\partial t}\right)_{k-1, l-1}^n = \frac{r_{k-1, l-1}^n L_{k-1, l-1}^n}{w_{k-1, l-1}^0} , \end{array} \right.$$

from which the velocities are derived:

$$(28) \quad \left\{ \begin{array}{l} u_{k-1, l-1}^{n + \frac{1}{2}} = u_{k-1, l-1}^{n - \frac{1}{2}} + \left(\frac{\partial u}{\partial t}\right)_{k-1, l-1}^n \Delta t^n , \\ v_{k-1, l-1}^{n + \frac{1}{2}} = v_{k-1, l-1}^{n - \frac{1}{2}} + \left(\frac{\partial v}{\partial t}\right)_{k-1, l-1}^n \Delta t^n . \end{array} \right.$$

This completes the evaluation of all points away from the explosion gas-air boundaries.

Each network point k, l is examined to determine if it crosses any boundary. Proceeding on successive constant Z or l lines from $R = 0$ to $R > 0$ (Figure 4), starting from a negative $Z < (z_b^0 - r_b^0)$ to some positive $Z > (z_a^0 + r_a^0)$, the $R = 0$ point has entered the domain of the explosion gas b whenever

$$z_b^0 - r_b^0 \leq Z_{o,l} \leq z_b^0 + r_b^0 ,$$

and has entered the domain of the explosion gas a whenever

$$z_a^0 - r_a^0 \leq Z_{o,l} \leq z_a^0 + r_a^0 .$$

If the $R = 0$ point is inside the explosion gas b , along each $Z_{k,l} = Z_{o,l} = \text{constant}$ line, the inequality

$$R_{k,l}^2 - \left[(r_b^0)^2 - (Z_{o,l} - z_b^0)^2 \right] \leq 0 ,$$

obtained using (9) must hold as $R_{k,l}$ increases. If the inequality holds, R is inside the explosion gas b ; otherwise, R is in air. Similarly, if the $R = 0$ point is inside the explosion gas a , along each $Z_{k,l} = Z_{o,l} = \text{constant}$ line, if

$$R_{k,l}^2 - \left[(r_a^0)^2 - (Z_{o,l} - z_a^0)^2 \right] \leq 0 .$$

is satisfied, R is inside a , and outside, if the inequality fails.

At any stage where R traverses an explosion gas boundary into air, J, K, L are evaluated by taking finite difference quotients across this discontinuity boundary. While this procedure is not exact, the error committed attenuates with propagation into the flow field.

CONCLUSION

The new BRLESC computing machine of BRL, with addition times in micro-seconds, can compute very rapidly the three dimensional network required in the numerical scheme of this problem. While the extensive information-hunting and reading with the magnetic tape will slow the overall computation considerably, a total of 52,000 fast core memory will be available soon, making the problem entirely feasible and the computing time very fast.

R.C. Makino

R. C. MAKINO

REFERENCES

1. Armendt, B. F., Hippensteel, R. G., Hoffman, A. J. and Kingery, C. N. The Air Blast from Simultaneously Detonated Explosive Spheres. BRL Memorandum Report No. 1294, Aberdeen Proving Ground, Maryland, August 1960.
2. Armendt, B. F., Hippensteel, R. G., Hoffman, A. J. and Keefer, J. H. Project White Tribe: Air Blast from Simultaneously Detonated Large-Scale Explosive Charges. BRL Report No. 1145, Aberdeen Proving Ground, Maryland, September 1961.
3. Armendt, B. F., Hippensteel, R. G., Hoffman, A. J. and Schlueter, S. D. The Air Blast from Simultaneously Detonated Explosive Spheres: Part II Optimization. BRL Memorandum Report No. 1384, Aberdeen Proving Ground, Maryland, January 1962.
4. von Neuman, J. and Richtmyer, R. D. A Method for the Numerical Calculations of Hydrodynamic Shocks. Journal of Applied Physics, 21, pp. 232-237, 1950.
5. Orlow, T., Piacesi, D. and Sternberg, H. M. A Computer Program for the Analysis of Transient, Axially Symmetric, Explosion and Shock Dynamics Problems. NAVWEPS Report 7265, U. S. Naval Ordnance Laboratory, White Oak, Maryland, December 1960.
6. Enig, J. W. Stability Criteria for Numerical Solutions in Unsteady Two-Dimensional Cylindrical Lagrange Flow. Journal of Mathematics and Physics, Vol. XL, No. 1, pp. 23-32, April 1961.
7. Kolsky, H. G. A Method for the Numerical Solution of Transient Hydrodynamic Shock Problems in Two Space Dimensions. LA-1867, Los Alamos Scientific Laboratory, Los Alamos, New Mexico, September 1954.
8. Taylor, G. I. The Dynamics of the Combustion Products Behind Plane and Spherical Detonation Fronts in Explosives. Proc. Roy. Soc. (London) A-200, 1950, p. 235.

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
10	Commander Armed Services Technical Information Agency ATTN: TIPCR Arlington Hall Station Arlington 12, Virginia	1	Research Analysis Corporation ATTN: Document Control Office 6935 Arlington Road Bethesda, Maryland Washington 14, D. C.
1	Director IDA/Weapon Systems Evaluation Group Room 1E875, The Pentagon Washington 25, D. C.	1	Commanding General White Sands Missile Range ATTN: ORDBS-OM- Technical Library RR-10 New Mexico
1	Director of Defense Research and Engineering (OSD) ATTN: Director/Ordnance Washington 25, D. C.	1	Army Research Office 3045 Columbia Pike Arlington, Virginia
2	Commanding General U. S. Army Materiel Command ATTN: AMCRD-RS-PE-Bal Research and Development Directorate Washington 25, D. C.	3	Chief, Bureau of Naval Weapons ATTN: DIS-33 Department of the Navy Washington 25, D. C.
1	Commanding General Frankford Arsenal ATTN: Library Branch 0270, Bldg 40 Philadelphia 37, Pennsylvania	1	Chief of Naval Operations Department of the Navy Washington 25, D. C.
3	Commanding Officer Picatinny Arsenal ATTN: Feltman Research and Engineering Laboratories Dover, New Jersey	2	Commander U. S. Naval Ordnance Laboratory ATTN: Mr. William Filler Mr. Peter Hanlon White Oak Silver Spring 19, Maryland
1	Commanding Officer Harry Diamond Laboratories ATTN: Technical Information Office Branch 012 Washington 25, D. C.	1	Commanding Officer Naval Ordnance Laboratory ATTN: Dr. H. A. Thomas Corona, California
		2	Commander U. S. Naval Ordnance Test Station ATTN: Technical Library China Lake, California

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Commanding Officer Naval Air Development Center Johnsville, Pennsylvania	1	FTD (TD-B1) Wright-Patterson Air Force Base Ohio
2	Commander U. S. Naval Weapons Laboratory Dahlgren, Virginia	1	SSD Air Force Unit Post Office Los Angeles 45, California
2	AUL (3T-AUL-60-118) Maxwell Air Force Base Alabama	1	Director, Project RAND Department of the Air Force 1700 Main Street Santa Monica, California
2	AFSC (SCRR) Andrews Air Force Base Washington 25, D. C.	5	Hq, USAF (AFDRT, AFCEA, AFORQ, AFDRD) Washington, 25, D. C.
1	AEDC (AEOI) Arnold Air Force Station Tullahoma, Tennessee	1	Sandia Corporation ATTN: Technical Library Sandia Base, New Mexico
1	APGC (PGAPI) Eglin Air Force Base Florida	3	University of California Lawrence Radiation Laboratory Technical Information Division ATTN: Clovis G. Craig P. O. Box 808 Livermore, California
	Of Interest to:		Of Interest to:
	PGTWR PGTW		Dr. Sidney Fernbach Dr. John Foster Mr. Bruce Crowley
2	AFCRL (CRRDM) ATTN: Lt. G. Meltz L. G. Hanscom Field Bedford, Massachusetts	4	U. S. Atomic Energy Commission Los Alamos Scientific Laboratory P. O. Box 1663 Los Alamos, New Mexico
1	AFMTC (MRSS) ATTN: J. R. Atkins Patrick Air Force Base Florida	1	Director National Aeronautics and Space Administration 1520 H Street Washington 25, D. C.
3	ASD (WWAD, WWY, WWDS) Wright-Patterson Air Force Base Ohio		

DISTRIBUTION LIST

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
1	Director National Aeronautics and Space Administration Langley Research Center ATTN: Mr. Pierce Langley Field, Virginia	1	Chance-Vought Aircraft Company ATTN: Dr. C. C. Wan P. O. Box 5907 Dallas, Texas
1	Aerojet-General Corporation 6352 North Irwindale Road Azusa, California	1	CONVAIR, A Division of General Dynamics Corporation P. O. Box 1950 San Diego 12, California
1	Aerojet-General Corporation Sacramento Plant ATTN: R. G. Weitz P. O. Box 1947 Sacramento 9, California	1	CONVAIR, A Division of General Dynamics Corporation Fort Worth 1, Texas
2	Aircraft Armaments, Inc. ATTN: Mr. R. R. Mills Dr. W. Baker P. O. Box 126 Cockeysville, Maryland	1	Cornell Aeronautical Laboratory, Inc. ATTN: Mr. J. Desmond, Librarian Buffalo 5, New York
1	Armour Research Foundation Illinois Institute of Technology Center ATTN: F. Porzel Chicago 16, Illinois	1	Douglas Aircraft Company Long Beach, California
1	Boeing Airplane Company ATTN: Mr. W. A. Pearce Wichita, Kansas	3	General Electric Company P. O. Box 1088 Schenectady 5, New York
2	Boeing Airplane Company ATTN: Mr. J. Christian Armament Unit Mr. R. M. Elain Aero Space Division Seattle 14, Washington	1	General Electric Company Technical Military Planning Operation ATTN: G. M. Shindler Drawer QQ Santa Barbara, California
1	Broadview Research Corporation ATTN: Kenneth Kaplan 1811 Trousdale Drive Burlingame, California	1	Grumman Aircraft Engineering Corporation ATTN: Armament Group Bethpage, Long Island, New York
		1	Hughes Aircraft Company ATTN: Mr. Dana Johnson Research and Development Laboratories Culver City, California

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Lockheed Aircraft Corporation ATTN: Mr. R. A. Bailey Division Engineer Military Operations Research Division Burbank, California	1	Applied Physics Laboratory The Johns Hopkins University 8621 Georgia Avenue Silver Spring, Maryland
2	The Martin Company ATTN: Mr. S. L. Rosing Mail No. 356 Middle River, Maryland Mr. Dobray Mail No. X813 Baltimore 3, Maryland	1	Guggenheim Aeronautical Laboratory California Institute of Technology ATTN: H. W. Leipmann Pasadena, California
1	McDonnell Aircraft Corporation ATTN: Armament Group P. O. Box 516 St. Louis 3, Missouri	1	James Forrestal Research Center Department of Aeronautical Engineering ATTN: Mr. Robert McAlevy Princeton, New Jersey
3	North American Aviation, Inc. ATTN: Mr. D. H. Mason Mr. J. Ward Engineering Technical File 12214 Lakewood Boulevard Downey, California	1	The Johns Hopkins University Institute for Cooperative Research 3506 Greenway Baltimore 18, Maryland
1	Northrop Aircraft, Inc. 1001 E. Broadway Hawthorne, California	2	Massachusetts Institute of Technology ATTN: Dr. James Mar Bldg 23-111 Dr. Emmett A. Witmer Room 41-219 Cambridge 39, Massachusetts
2	Republic Aviation Corporation Farmingdale, Long Island, New York	1	Massachusetts Institute of Technology Aeroelastic and Structures Research Laboratory Cambridge, Massachusetts
2	The Rand Corporation ATTN: H. L. Brode F. R. Gilmore 2500 Colorado Avenue Santa Monica, California	1	Midwest Research Institute ATTN: B. L. Rhodes 425 Volker Boulevard Kansas City 10, Missouri
1	Space Technology Laboratories, Inc. ATTN: Technical Information Center P. O. Box 95001 Los Angeles 45, California	1	Purdue University Director of Statistical Laboratory ATTN: Dr. Kossach Lafayette, Indiana

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Stanford Research Institute Menlo Park, California	1	Professor N. Davids Department of Engineering Mechanics Pennsylvania State University University Park, Pennsylvania
1	Stevens Institute of Technology Davidson Laboratory ATTN: Mr. L. H. Weeks Castle Point Station Hoboken, New Jersey	1	Professor M. Holt Brown University Graduate Division of Applied Mathematics Providence, Rhode Island
1	University of Utah Institute of Rate Processes ATTN: M. A. Cook Salt Lake City, Utah	1	Professor J. P. Hirschfelder University of Wisconsin Naval Research Laboratory Madison, Wisconsin
1	University of Michigan Department of Engineering ATTN: Dr. O. Laporte Ann Arbor, Michigan	1	Dr. J. S. Rinehart University of Colorado School of Mines Golden, Colorado
1	Professor W. Bleakney Palmer Physical Laboratory Princeton University Princeton, New Jersey	1	Mr. R. McAievy Princeton University Forrestal Research Center Department of Aeronautical Engineering Princeton, New Jersey
1	Dr. S. R. Brinkley Combustion and Explosives Research, Inc. Alcoa Building Pittsburgh 19, Pennsylvania	1	Professor W. Sears Cornell University Graduate School of Aeronautical Engineering Ithaca, New York
5	Mr. Benjamin Day 164 Cornell Quarters Ithaca, New York		
1	Professor K. O. Friedrichs New York University Applied Mathematics Panel New York, New York	1	Professor G. B. Whitham New York University Institute of Mathematical Science 25 Waverly Place New York 3, New York

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>
10	The Scientific Information Officer Defence Research Staff British Embassy ATTN: Reports Officer 3100 Massachusetts Avenue, N.W. Washington 8, D. C. Of Interest to: Mr. G. Simm R.A.E.
4	Defence Research Member Canadian Joint Staff 2450 Massachusetts Avenue, N.W. Washington 8, D. C.

AD	Accession No.	UNCLASSIFIED	AD	Accession No.	UNCLASSIFIED
AD	Ballistic Research Laboratories, APC	Air Blast - Pressure Explosions - Blast	AD	Ballistic Research Laboratories, APC	Air Blast - Pressure Explosions - Blast
A METHOD FOR COMPUTING THE INTERACTION OF TWO SPHERICAL BLAST WAVES			A METHOD FOR COMPUTING THE INTERACTION OF TWO SPHERICAL BLAST WAVES		
R. C. Makino			R. C. Makino		
ERL Memorandum Report No. 1462 March 1963			ERL Memorandum Report No. 1462 March 1963		
RD & E Project No. 1M010501A006			RD & E Project No. 1M010501A006		
UNCLASSIFIED Report			UNCLASSIFIED Report		
The artificial viscosity method of von Neumann and Richtmyer for numerical solution of the partial differential equations of fluid flow is used to obtain a scheme for the numerical calculation of the interaction of two spherical blast waves in air.			The artificial viscosity method of von Neumann and Richtmyer for numerical solution of the partial differential equations of fluid flow is used to obtain a scheme for the numerical calculation of the interaction of two spherical blast waves in air.		
AD	Accession No.	UNCLASSIFIED	AD	Accession No.	UNCLASSIFIED
AD	Ballistic Research Laboratories, APC	Air Blast - Pressure Explosions - Blast	AD	Ballistic Research Laboratories, APC	Air Blast - Pressure Explosions - Blast
A METHOD FOR COMPUTING THE INTERACTION OF TWO SPHERICAL BLAST WAVES			A METHOD FOR COMPUTING THE INTERACTION OF TWO SPHERICAL BLAST WAVES		
R. C. Makino			R. C. Makino		
ERL Memorandum Report No. 1462 March 1963			ERL Memorandum Report No. 1462 March 1963		
RD & E Project No. 1M010501A006			RD & E Project No. 1M010501A006		
UNCLASSIFIED Report			UNCLASSIFIED Report		
The artificial viscosity method of von Neumann and Richtmyer for numerical solution of the partial differential equations of fluid flow is used to obtain a scheme for the numerical calculation of the interaction of two spherical blast waves in air.			The artificial viscosity method of von Neumann and Richtmyer for numerical solution of the partial differential equations of fluid flow is used to obtain a scheme for the numerical calculation of the interaction of two spherical blast waves in air.		